

ANCHOR UPSTREAM END OF WALL WITH LARGE, SANDSTONE OR GLACIAL BOULDERS, BURY TO ELEVATION 5685 MIN.

TW 5697.65
5695
5693.5
5692
5690
BW 5687.5


TW 5696
5694.5
5693
5691.5
5689.5
BW 5687

BOULDERS NOT IN THE PREMIUM ZONE SHALL FALL WITHIN THE FOLLOWING PARAMETERS:

1. MAXIMUM RISER HEIGHT OF 36", TREAD WIDTH BETWEEN 24" AND 48", ANY LENGTH
2. HEIGHT VARIATIONS BETWEEN ADJACENT BOULDERS NOT TO VARY MORE THAN 8"
3. SET BOULDERS FOR OPTIMUM STABILITY AND VISUAL AESTHETICS.
4. MEET SPOT GRADES AT TOP AND BOTTOM OF WALL AND MAINTAIN CONSISTENT SLOPES, ELIMINATE ROWS AS NECESSARY.

INTERMEDIATE SANDSTONE STEPS TO BE ANCHORED BETWEEN LARGE BOULDERS. RISER HEIGHT BETWEEN 6"-12". PREMIUM SANDSTONE BOULDERS SHALL FALL WITHIN THE FOLLOWING PARAMETERS:

1. PREMIUM BOULDERS ARE CUBICLE WITH DIMENSIONS; 18"-30" HEIGHT, x 24"-36" TREAD WIDTH, x ANY LENGTH.
2. HEIGHT VARIATIONS BETWEEN ADJACENT BOULDERS NOT TO VARY MORE THAN 2"



SCALE: 1"=10'-0"

FEBRUARY 8, 2010